

NEK2160U



**ENGINEERING CODE**  
863FA51



**REFRIGERANT**  
R-290



**POWER SUPPLY**  
220-240 V 50 Hz



**APPLICATION**  
LBP



**MOTOR TYPE**  
CSCR



**STANDARD**  
EN12900



**COOLING CAPACITY**  
419 W



**EFFICIENCY**  
1.18 W/W



DATA

GENERAL DATA

Model	NEK2160U
Type	Hermetic Reciprocating
Technology	ON/OFF
Compressor Application	LBP
Expansion Device	Capillary Tube or Expansion Valve
Compressor Cooling	Fan/220
HP	3/4
Starting Torque	HST
Plant	SLOVAKIA

ELECTRICAL DATA

Start Winding Resistance	11.7 Ω at 25°C
Run Winding Resistance	3.96 Ω at 25°C
Locked Rotor Amperage (LRA) 50Hz	18 A

## MECHANICAL DATA

Displacement	16.8 cm <sup>3</sup>
Oil Charge	350 ml
Oil Type	AB
Oil Viscosity	ISO32
Weight	11.9 Kg

## ELECTRICAL COMPONENTS

Start Capacitor	53-64 µf/330 V
Run Capacitor	10.0 µf/440 V
CSR CSIR BOX	Yes
Starting Device Description	RVA2L3C
Overload Protection	T0660/G9

## EXTERNAL CHARACTERISTICS

Base Plate	SMALL
Tray Holder	NO

Connector	Internal Diameter	Shape	Material
Suction	8.1 mm	SLANTED 42°	COPPER
Discharge	6.1 mm	STRAIGHT	COPPER
Process	6.1 mm	SLANTED 42°	COPPER

## PERFORMANCE

### TESTED CONDITIONS

Tested Refrigerant	R-290
Tested Application	LBP
Tested Standard	EN12900
Tested Cooling	Fan
Tested Voltage	220 V
Tested Frequency	50 Hz
Refrigerant Temperature	Dew

**RATED POINTS**

Condensing Temperature °C	Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
40	-35	419	1.18	355	-	4.81

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

**PERFORMANCE CURVE****Condensing Temperature 35°C**

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-40	348	1.13	308	-	3.81
-35	452	1.30	347	-	4.96
-30	581	1.49	389	-	6.40
-25	737	1.70	434	-	8.14
-20	920	1.93	478	-	10.20
-15	1130	2.18	519	-	12.58
-10	1366	2.46	556	-	15.30

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

**PERFORMANCE CURVE****Condensing Temperature 45°C**

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-40	298	0.93	322	-	3.58
-35	387	1.07	362	-	4.65
-30	498	1.22	409	-	6.02
-25	634	1.37	462	-	7.68
-20	793	1.53	518	-	9.65
-15	977	1.70	574	-	11.95
-10	1184	1.89	628	-	14.58

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

**PERFORMANCE CURVE****Condensing Temperature 55°C**

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-30	413	0.99	419	-	5.56
-25	528	1.11	477	-	7.13
-20	664	1.23	541	-	9.00
-15	821	1.35	609	-	11.20
-10	999	1.47	679	-	13.73

Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.

## ENVELOPE



## EXTERNAL DIMENSIONS

