

Artikelnummer / Article number: LF1120318

DEU

MAGNETVENTIL PARKER 2 WEGE \varnothing 1/8"F 220V
201XGIAGV7-F - Anschlüsse \varnothing 1/8"FF - max 14 bar
Dichtung aus VITON - Öffnung \varnothing 2,5 mm
mit Spule 483510S6 XS03XS6 F 9W 220/240V 50/60Hz
Flüssigkeittemperatur -40°C+140°C

ENU

SOLENOID VALVE PARKER 2 W. \varnothing 1/8"F 220V
201XGIAGV7-F - fittings \varnothing 1/8"FF - max 14 bar
VITON seal - orifice \varnothing 2.5 mm
with coil 483510S6 XS03XS6 F 9W 220/240V 50/60Hz
fluids temperature -40°C+140°C

ESP

ELETTROVALVOLA PARKER 2 VIE \varnothing 1/8"F 220V
201XGIAGV7-F - conexiones \varnothing 1/8"FF - max 14 bar
estanqueidad de VITON - orificio \varnothing 2,5 mm
con bobina 483510S6 XS03XS6 F 9W 220/240V 50/60Hz
temperatura fluidi -40°C+140°C

FRA

ELECTROVANNE PARKER 2 VOIES \varnothing 1/8"F 220V
201XGIAGV7-F - raccords \varnothing 1/8"FF - max. 14 bar
joint en VITON - orifice \varnothing 2,5 mm
avec bobine 483510S6 XS03XS6 F 9W 220/240V 50/60Hz
température fluides -40°C+140°C

ITA

ELETTROVALVOLA PARKER 2 VIE \varnothing 1/8"F 220V
201XGIAGV7-F - attacchi \varnothing 1/8"FF - max 14 bar

tenuta in VITON - orificio \varnothing 2,5 mm

con bobina 483510S6 XS03XS6 F 9W 220/240V 50/60Hz

temperatura fluidi $-40^{\circ}\text{C}+140^{\circ}\text{C}$